

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Trade name	: iLAST POWER STEERING FLUID 12 FL.OZ.
Product code	: FPIL0008
Other means of identification	: This product is not hazardous in accordance with US OSHA 29CFR1910.1200 (Hazcom 2012), Canada Hazardous Products Regulations (WHMIS 2015) and the Globally Harmonized System (GHS).

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Power Steering Fluid
------------------------------	------------------------

#### 1.3. Details of the supplier of the safety data sheet

US Global Petroleum  
9101 Fullerton Avenue  
Franklin Park, IL 60131 - USA  
T 773-376-9660

#### 1.4. Emergency telephone number

Emergency number	: CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)
------------------	---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Not classified

#### 2.2. Label elements

##### GHS US labeling

No labeling applicable

#### 2.3. Other hazards

Other hazards which do not result in classification	: None under normal conditions.
---	---------------------------------

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS-No.) 64742-52-5	≥ 95	Asp. Tox. 1, H304
Diisodecyl Adipate	(CAS-No.) 27178-16-1	< 1	Not classified
Lubrizol Additive		< 1	Skin Sens. 1, H317 Carc. 1B, H350
White Mineral Oil (Petroleum)	(CAS-No.) 8042-47-5	0.03 – 0.06	Asp. Tox. 1, H304
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based	(CAS-No.) 72623-86-0	0.03 – 0.06	Carc. 1B, H350
Paraffinum Liquidum	(CAS-No.) 8012-95-1	0.03 – 0.06	Not classified
	(CAS-No.) 64742-54-7	0.01 – 0.02	Carc. 1B, H350
Petroleum Naphtha	(CAS-No.) 64742-47-8	< 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/effects after inhalation : May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/effects after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
- Symptoms/effects after eye contact : May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.
- Symptoms/effects after ingestion : May be harmful if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Insufficient data available on direct fire hazard (flashpoint > 200°C).

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Remove contaminated clothes. Wash contaminated clothing before reuse. Always wash hands after handling the product. Wash affected areas thoroughly after handling. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from	: Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.	
Incompatible materials	: Sources of ignition. Direct sunlight.	

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>iLAST POWER STEERING FLUID 12 FL.OZ.</b>	
No additional information available	
<b>Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	5 mg/m <sup>3</sup> MIST 8 HOURS
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL (TWA) [1]	5 mg/m <sup>3</sup> MIST 8 HOURS
<b>Petroleum Naphtha (64742-47-8)</b>	
No additional information available	
<b>White Mineral Oil (Petroleum) (8042-47-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	5 mg/m <sup>3</sup> (Inhalable fraction)
ACGIH OEL STEL	10 mg/m <sup>3</sup>
<b>Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)</b>	
No additional information available	
<b>Paraffinum Liquidum (8012-95-1)</b>	
No additional information available	
<b>Lubrizol Additive</b>	
No additional information available	
<b>Diisodecyl Adipate (27178-16-1)</b>	
No additional information available	
<b>(64742-54-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	5 mg/m <sup>3</sup> (Mineral oil, pure, highly and severely refined; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

#### Materials for protective clothing:

No data available

#### Hand protection:

Wear protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear appropriate mask

#### Personal protective equipment symbol(s):

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless to yellow.
Odor	: Petroleum-like odour.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 204 °C
Flash point	: > 94 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.88
Solubility	: Poorly soluble in water. Water: < 4 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 21.6 cSt @ 40 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content	: < 2 %
-------------	---------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)</b>	
LD50 oral rat	> 5000 mg/kg body weight

<b>White Mineral Oil (Petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))

<b>(64742-54-7)</b>	
LD50 oral rat	> 5000 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	> 5.53 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : 21.6 mm<sup>2</sup>/s @ 40 deg C

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation : May cause an allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.

Symptoms/effects after eye contact : May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.

Symptoms/effects after ingestion : May be harmful if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>White Mineral Oil (Petroleum) (8042-47-5)</b>	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

<b>(64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)
Threshold limit - Algae [1]	≥ 100 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>iLAST POWER STEERING FLUID 12 FL.OZ.</b>	
Persistence and degradability	Not established.

<b>Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)</b>	
Persistence and degradability	Not established.

<b>Petroleum Naphtha (64742-47-8)</b>	
Persistence and degradability	Not established.

<b>White Mineral Oil (Petroleum) (8042-47-5)</b>	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil. Not established.

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)</b>	
Persistence and degradability	Not established.
<b>Paraffinum Liquidum (8012-95-1)</b>	
Persistence and degradability	Not established.
<b>Diisodecyl Adipate (27178-16-1)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>(64742-54-7)</b>	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil.

### 12.3. Bioaccumulative potential

<b>iLAST POWER STEERING FLUID 12 FL.OZ.</b>	
Bioaccumulative potential	Not established.
<b>Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)</b>	
Bioaccumulative potential	Not established.
<b>Petroleum Naphtha (64742-47-8)</b>	
Bioaccumulative potential	Not established.
<b>White Mineral Oil (Petroleum) (8042-47-5)</b>	
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.18 (Experimental value)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5). Not established.
<b>Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)</b>	
Bioaccumulative potential	Not established.
<b>Paraffinum Liquidum (8012-95-1)</b>	
Bioaccumulative potential	Not established.
<b>Diisodecyl Adipate (27178-16-1)</b>	
BCF - Fish [1]	34.4 – 316 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	9.56 – 10.4 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>(64742-54-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

### 12.4. Mobility in soil

<b>White Mineral Oil (Petroleum) (8042-47-5)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.64 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
<b>Diisodecyl Adipate (27178-16-1)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5.827 – 6.992 (log Koc, Calculated value)
Ecology - soil	Adsorbs into the soil.

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with local/national regulations.
- Ecology - waste materials : Avoid release to the environment.

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not regulated

#### Transport by sea

#### Air transport

Proper Shipping Name (IATA) : Not Regulated

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### iLAST POWER STEERING FLUID 12 FL.OZ.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

##### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
-------------------------------------	---------------------------------

##### Petroleum Naphtha (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard
-------------------------------------	--

##### White Mineral Oil (Petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Paraffinum Liquidum (8012-95-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Diisodecyl Adipate (27178-16-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

##### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

Listed on the Canadian DSL (Domestic Substances List)

##### Petroleum Naphtha (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

##### White Mineral Oil (Petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

##### Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

Listed on the Canadian DSL (Domestic Substances List)

##### Paraffinum Liquidum (8012-95-1)

Listed on the Canadian DSL (Domestic Substances List)

##### Diisodecyl Adipate (27178-16-1)

Listed on the Canadian DSL (Domestic Substances List)

##### (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

##### Petroleum Naphtha (64742-47-8)

##### White Mineral Oil (Petroleum) (8042-47-5)

##### Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Paraffinum Liquidum (8012-95-1)**

**Diisodecyl Adipate (27178-16-1)**

**(64742-54-7)**

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

**Petroleum Naphtha (64742-47-8)**

**White Mineral Oil (Petroleum) (8042-47-5)**

**Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)**

**Paraffinum Liquidum (8012-95-1)**

**Diisodecyl Adipate (27178-16-1)**

**(64742-54-7)**

#### 15.3. US State regulations

##### iLAST POWER STEERING FLUID 12 FL.OZ.( )

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65

##### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

##### Petroleum Naphtha (64742-47-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

##### White Mineral Oil (Petroleum) (8042-47-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

##### Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

##### Paraffinum Liquidum (8012-95-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	



# iLAST POWER STEERING FLUID 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diisodecyl Adipate (27178-16-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

(64742-54-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Petroleum Naphtha (64742-47-8)				
State or local regulations				
U.S. – New York City – Right to Know Hazardous Substances List				

Paraffinum Liquidum (8012-95-1)				
State or local regulations				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				


## SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H350	May cause cancer

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.  
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible  
Flammability : 1 Slight Hazard  
Physical : 0 Minimal Hazard  
Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.