

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/11/2022 Version: 1.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Product name : ILAST BRAKE CLEANER NON-CHLORINATED 45% VOC 14 OZ.

Product code : FPiL0021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Parts Cleaner

Details of the supplier of the safety data sheet

US Global Petroleum 9101 Fullerton Avenue Franklin Park, IL 60131 - USA

T 773-376-9660

Emergency telephone number

: CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International) **Emergency number**

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 2 Gases under pressure Compressed gas Acute toxicity (oral) Category 3

Acute toxicity (dermal) Category 3 Skin corrosion/irritation Category 2

Precautionary statements (GHS US)

Serious eye damage/eye irritation Category 2A Specific target organ toxicity (single exposure) Category 1

Specific target organ toxicity — Single exposure, Category 3, Narcosis

H223 Flammable aerosol

H280 Contains gas under pressure; may explode if heated

H301 Toxic if swallowed H311 Toxic in contact with skin H315 Causes skin irritation

H319 Causes serious eye irritation H370 Causes damage to organs

H336 May cause drowsiness or dizziness

Full text of H- and EUH-statements: see section 16

Label elements 2.2.

GHS US labeling

Hazard pictograms (GHS US)











Signal word (GHS US) : Danger

Hazard statements (GHS US) H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness H370 - Causes damage to organs

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use.

P260 - Do not breathe dust, fumes, gas, mist, vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P307+P311 - If exposed: Call a poison center/doctor.

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P321 - Specific treatment: See section 4.1 on SDS

P322 - Specific treatment (see supplemental first aid instruction on this label)

EN (English US) 11/04/2022 1/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards which do not result in classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	(CAS-No.) 67-64-1	85 – 95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methanol	(CAS-No.) 67-56-1	10 – 30	Flam. Liq. 2, H225 STOT SE 1, H370
Heptane, Branched Cyclic	(CAS-No.) 426260-76-6	12.24 – 12.75	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 – 10	Press. Gas (Comp.), H280
n-Heptane	(CAS-No.) 142-82-5	3.188 – 5.738	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SECTION 4: First aid measures

First-aid measures after inhalation

First-aid measures after skin contact

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention. Call a POISON CENTER or doctor/physician.

: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call

a POISON CENTER or doctor/physician if you feel unwell.

: Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with

water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be

irritating.

First-aid measures after ingestion

Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation

: Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact

: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact

: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

Symptoms/effects after ingestion

: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

11/04/2022 EN (English US) 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of **Explosion hazard**

burns and injuries.

Advice for firefighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information Aerosol Level 2.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove General measures

ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray. Protective equipment

Emergency procedures Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

: Dam up the liquid spill. Plug the leak, cut off the supply. Contain released product, collect/pump For containment

into suitable containers.

Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or Additional hazards when processed

burn, even after use.

Wash hands and other exposed areas with mild soap and water before eating, drinking or Precautions for safe handling

> smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe

dust,fumes,gas,mist,vapor spray.

Wash contaminated clothing before reuse. Always wash hands after handling the product. Hygiene measures Remove contaminated clothes. Separate working clothes from town clothes. Launder

separately. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact. Observe very strict hygiene - avoid contact. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.

Conditions for safe storage, including any incompatibilities

: Proper grounding procedures to avoid static electricity should be followed. Technical measures

Keep only in the original container in a cool, well ventilated place away from : Do not expose to Storage conditions

temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products Strong bases. Strong acids.

: Sources of ignition. Direct sunlight. Heat sources. Incompatible materials

Store in a well-ventilated place Storage area

Specific end use(s)

Follow Label Directions.

11/04/2022 EN (English US) 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ILAST BRAKE CLEANER NON-CHLORINATED 4	5% VOC 14 OZ.
No additional information available	
n-Heptane (142-82-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	400 ppm
ACGIH OEL STEL [ppm]	500 ppm
Heptane, Branched Cyclic (426260-76-6)	1 Ph.
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	400 ppm
ACGIT OLL TWA [ppin] ACGIH OEL STEL [ppm]	500 ppm
USA - OSHA - Occupational Exposure Limits	300 ррні
•	500 nnm
OSHA PEL (TWA) [2]	500 ppm
Carbon Dioxide, Liquefied, Under Pressure (124	-38-9)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	9000 mg/m³
ACGIH OEL TWA [ppm]	5000 ppm
ACGIH OEL STEL	54000
ACGIH OEL STEL [ppm]	30000 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	9000 mg/m³
OSHA PEL (TWA) [2]	5000 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	9000 mg/m³
NIOSH REL TWA [ppm]	5000 ppm
NIOSH REL (Ceiling)	54000 mg/m³
NIOSH REL C [ppm]	30000 ppm
Methanol (67-56-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	262 mg/m³
	202 mg/m²
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL TWA [ppm]	200 ppm 328 mg/m³
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm]	200 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits	200 ppm 328 mg/m³ 250 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2]	200 ppm 328 mg/m³ 250 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA)	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL TWA [ppm]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL TWA [ppm] NIOSH REL (Ceiling)	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL TWA [ppm] NIOSH REL (Ceiling) NIOSH REL C [ppm]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL TWA [ppm] NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1)	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL TWA [ppm] NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] ACGIH OEL TWA [ppm]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm 1782 mg/m³
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL TWA [ppm]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm 1782 mg/m³ 750 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm 1782 mg/m³ 750 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm 1782 mg/m³ 750 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm 1782 mg/m³ 750 ppm 2400 mg/m³ 1000 ppm
ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] USA - NIOSH - Occupational Exposure Limits NIOSH REL (TWA) NIOSH REL (TWA) NIOSH REL (Ceiling) NIOSH REL (Ceiling) NIOSH REL C [ppm] Acetone (67-64-1) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL ACGIH OEL STEL [ppm] USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1]	200 ppm 328 mg/m³ 250 ppm 260 mg/m³ 200 ppm 260 mg/m³ 200 ppm 325 mg/m³ 250 ppm 1188 mg/m³ 500 ppm 1782 mg/m³ 750 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

11/04/2022 EN (English US) 4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Materials for protective clothing:

GIVE EXCELLENT RESISTANCE:

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):





Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color
Color
Color
Codor
Codor
Codor threshold

Freezing point : < -78 °C (Lowest Component-Acetone)

Boiling point : 56.1 °C (Lowest Component-Acetone)

Flash point : -18 °C (Lowest Component-Acetone)

Auto-ignition temperature : 385 °C (Lowest Component-Acetone)

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 0.82

Solubility : Poorly soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Partition coefficient n-octanol/water (Log Kow) : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : Heating may cause a fire or explosion.

Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

VOC content : 45 %

Gas group : Compressed gas

11/04/2022 EN (English US) 5/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed.

Acute toxicity (dermal) : Toxic in contact with skin.

Acute toxicity (inhalation) : Not classified

n Hantana (440.00 E)	
ATE US (dermal)	300 mg/kg body weight
ATE US (oral)	100 mg/kg body weight

n-Heptane (142-82-5)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Readacross, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 29.29 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))

Heptane, Branched Cyclic (42626	i0-76-6)
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Readacross, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 29.29 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))

Methanol (67-56-1)	
LD50 oral rat	≥ 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 Inhalation - Rat	128.2 mg/l/4h Air
ATE US (dermal)	17100 mg/kg body weight
ATE US (vapors)	128.2 mg/l/4h
ATE US (dust, mist)	128.2 mg/l/4h

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 Inhalation - Rat [ppm]	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (gases)	30000 ppmV/4h
ATE US (vapors)	71 mg/l/4h
ATE US (dust, mist)	71 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

11/04/2022 EN (English US) 6/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs. May cause drowsiness or dizziness.

STOT-single exposure	: Causes damage to organs. May cause drowsiness or dizziness.
n-Heptane (142-82-5)	
STOT-single exposure	May cause drowsiness or dizziness.
Heptane, Branched Cyclic (426260-76-6)	
STOT-single exposure	May cause drowsiness or dizziness.
Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/effects	: Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/effects after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

Causes serious eye irritation.

hazard.

Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

SECTION 12: Ecological information

Symptoms/effects after ingestion

12.1. Toxicity

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
LC50 - Fish [1]	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)
Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semistatic system, Fresh water, Experimental value, Locomotor effect)
Acetone (67-64-1)	
LC50 - Fish [1]	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 - Crustacea [1]	8800 mg/l (48 h; Daphnia pulex)
LC50 - Fish [2]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM - Fish [1]	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM - Fish [2]	> 1000 ppm (96 h; Pisces)
Threshold limit - Other aquatic organisms [1]	3000 mg/l (Plankton)
Threshold limit - Other aquatic organisms [2]	28 mg/l (Protozoa)
Threshold limit - Algae [1]	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit - Algae [2]	3400 mg/l (48 h; Chlorella sp.)

12.2. Persistence and degradability

ILAST BRAKE CLEANER NON-CHLORINATED 45% VOC 14 OZ.		
Persistence and degradability	Not established.	
n-Heptane (142-82-5)		
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established.	
Biochemical oxygen demand (BOD)	1.92 g O ₂ /g substance	
Chemical oxygen demand (COD)	0.06 g O ₂ /g substance	
ThOD	3.52 g O ₂ /g substance	
Heptane, Branched Cyclic (426260-76-6)		
Persistence and degradability	May cause long-term adverse effects in the environment.	

11/04/2022 EN (English US) 7/12

Other information

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Dioxido, Liquefied, Under Prossure (1	· · · · · · · · · · · · · · · · · · ·
Carbon Dioxide, Liquefied, Under Pressure (1	
Persistence and degradability Chemical oxygen demand (COD)	Biodegradability: not applicable. Not established. Not applicable (inorganic)
	Not applicable (inorganic) Not applicable (inorganic)
ThOD	Thou applicable (IIIOIgailic)
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
12.3. Bioaccumulative potential	
ILAST BRAKE CLEANER NON-CHLORINATE	D 45% VOC 14 OZ.
Bioaccumulative potential	Not established.
n-Heptane (142-82-5)	
BCF - Other aquatic organisms [1]	552 (BCFBAF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	4.66 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5). Not established.
Heptane, Branched Cyclic (426260-76-6)	
Bioaccumulative potential	Not established.
·	
Carbon Dioxide, Liquefied, Under Pressure (1	
Partition coefficient n-octanol/water (Log Pow)	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Methanol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
Acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative. Not established.
12.4. Mobility in soil	
n-Heptane (142-82-5)	
Surface tension	19.66 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
Carbon Dioxide, Liquefied, Under Pressure (1	
Ecology - soil	Not applicable (gas).
	1 abbaas.a (Ana).
Methanol (67-56-1) Surface tension	No data available in the literature
	No data available in the literature -0.89 – -0.21 (log Koc, Calculated value)
Partition coefficient n-octanol/water (Log Koc) Ecology - soil	Highly mobile in soil.
••	Tilgrily Tilouile III Suli.
Acetone (67-64-1)	0.0007 N/w /00.00\
Surface tension	0.0237 N/m (20 °C)
12.5. Other adverse effects	
Effect on global warming	· No known offacts from this product
Effect on global warming	: No known effects from this product.

EN (English US) 11/04/2022 8/12

: Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

Waste treatment methods

: Dispose in a safe manner in accordance with local/national regulations. Container under Product/Packaging disposal recommendations

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

US DOT (ground) (DOT) : UN1950 Aerosols (Flammable, (each not exceeding 1 L capacity)), 2.1, Limited Quantity

UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols

Flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115 Hazard labels (DOT) : LTD QTY - Limited quantity

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) 306 DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Other information : No supplementary information available.

Transport by sea

UN-No. (IMDG) : 1950

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : 1950 Proper Shipping Name (IATA) : Aerosols

Class (IATA) 2.1 - Gases : Flammable Hazard labels (IATA) : LTD QTY - Limited Quantity



SECTION 15: Regulatory information

15.1. US Federal regulations

ILAST BRAKE CLEANER NON-CHLORINATED 45% VOC 14 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
	Sudden release of pressure hazard

11/04/2022 9/12 EN (English US)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Heptane (142-82-5)					
Listed on the United States TSCA (Toxic Substances Control Act) inventory					
Heptane, Branched Cyclic (426260-76-6)					
Listed on the United States TSCA (Toxic Substances Control Act) inventory SARA Section 311/312 Hazard Classes Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard					
					Carbon Dioxide, Liquefied, Under Pressure (1
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory				
SARA Section 311/312 Hazard Classes Sudden release of pressure hazard Immediate (acute) health hazard					
Methanol (67-56-1)					
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313					
CERCLA RQ	5000 lb				
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard				
SARA Section 313 - Emission Reporting	1 %				
Acetone (67-64-1)					
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313					
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard					
5.2. International regulations					

CANADA

ILAST BRAKE CLEANER NON-CHLORINATE	O 45% VOC 14 OZ.					
WHMIS Classification	Class B Division 5 - Flammable Aerosol					
n-Heptane (142-82-5)						
Listed on the Canadian DSL (Domestic Substances List)						
Heptane, Branched Cyclic (426260-76-6)						
Listed on the Canadian DSL (Domestic Substance	ces List)					
WHMIS Classification Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects						
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)					
Listed on the Canadian DSL (Domestic Substance	ces List)					
Methanol (67-56-1)						
Listed on the Canadian DSL (Domestic Substance	es List)					
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects					
Acetone (67-64-1)						
Listed on the Canadian DSL (Domestic Substance	ces List)					
WHMIS Classification Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects						

EU-Regulations

Heptane, Branched Cyclic (426260-76-6)	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Methanol (67-56-1)	
Acetone (67-64-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

11/04/2022 EN (English US) 10/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. **National regulations**

Heptane, Branched Cyclic (426260-76-6)

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

ILAST BRAKE CLEANER NON-CHLORINATED 45% VOC 14 OZ.()					
U.S California - Proposition 65 - Carcinogens List	Yes				
U.S California - Proposition 65 - Developmental Toxicity	Yes				
U.S California - Proposition 65 - Reproductive Toxicity - Female	No				
U.S California - Proposition 65 - Reproductive Toxicity - Male	Yes				
State or local regulations	U.S California - Proposition 65				
n-Hantane (142-82-5)					

n-Heptane (142-82-5)	Heptane (142-82-5)								
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)					
No	No	No	No						

Heptane, Branched Cyclic (426260-76-6)							
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)			
No	No	No	No				

Carbon Dioxide, Liquefied,	, Under Pressure (124-38-9)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Methanol (67-56-1)					
	U.S California - Proposition 65 -	No significant risk level (NSRL)			
	Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	(NONE)
			Female	Male	
	No	Yes	No	No	

Acetone (67-64-1)						
	U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
	Yes	Yes	No	Yes		

n-Heptane (142-82-5)

State or local regulations

- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York City Right to Know Hazardous Substances List U.S. Pennsylvania RTK (Right to Know) List

11/04/2022 EN (English US) 11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

State or local regulations

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York City Right to Know Hazardous Substances List
- U.S. Pennsylvania RTK (Right to Know) List

Methanol (67-56-1)

State or local regulations

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York City Right to Know Hazardous Substances List

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65

Benzene 71-43-2

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H223	Flammable aerosol
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard	:	2	2 - Materials that,	under	emergency	conditions,	can	cause
--------------------	---	---	---------------------	-------	-----------	-------------	-----	-------

temporary incapacitation or residual injury.


NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended

solids) that can be ignited under almost all ambient

temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

11/04/2022 EN (English US) 12/12