

Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660

SN / CF
C2-16, C3-16

Premium
Performance

EVEREST®

Full Synthetic EUROLINE SAE 5W-30 Motor Oil

Everest Full Synthetic EuroLine SAE 5W-30 Motor Oil is a specialized multi-grade oil designed with a state-of-the-art low friction additive system to meet the latest stringent, high-performance European OEM standards for maximum engine performance, protection, and longevity even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against the build-up of performance robbing sludge and varnish deposits. It is recommended for turbo-charged and high-powered passenger car, light duty truck, sport utility vehicle and other mobile or stationary engines.

Everest Full Synthetic EuroLine SAE 5W-30 Motor Oil meets or exceeds SN / CF service classifications and is compatible with all prior categories. Everest Full Synthetic EuroLine SAE 5W-30 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA C2-16, C3-16, A3/B3, A3/B4, Chrysler, Ford, Porsche, Renault, VW, and other OEM's specifications where a full synthetic SN motor oil is recommended.

Benefits and Applications

- Designed especially for European gasoline and diesel engines
- Increases the DPF/GPF and TWC life and maintains the Vehicle's Fuel Economy
- More robust oil for longer drain intervals
- Enhanced oxidative stability, emission system and wear protection
- Maximum engine wear, corrosion, and rust protection and cleanliness
- Lower pour point reduces start-up wear during cold weather

5W-30 Typical Characteristics - V200617

SAE GRADE		5W-30
Service Grade		SN CF
ACEA Grade		C2-16, C3-16
API Gravity	ASTM D287	35.58
Flash Point, COC °C/°F	ASTM D92	227 / 440.6
Pour Point, °C/°F	ASTM D97	-45 / -49
Viscosity @ 40°C, cSt	ASTM D445	61.12
Viscosity @ 100°C, cSt	ASTM D445	10.93
Viscosity Index	ASTM D2270	169
CCS, mPa-sec °C max	ASTM D5293	6600 @ -30
Total Base No. TBN	ASTM D2896	10.5

Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

**Meets or Exceeds
SN / CF
ACEA C2-16, C3-16**
A3/B3-16, A3/B4-16, MB
229.31 v2016.1, MB 226.5,
Chrysler, Ford, Porsche,
Renault, VW, comparable to
BMW full synthetic SN
requirements.



REDUCED SAPS



HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.