

Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660

API SP

Premium
Performance

EVEREST®

Full Synthetic SAE 10W-40 Motor Oil

EVEREST Full Synthetic SAE 10W-40 Motor Oil is a superior quality multi-grade motor oil designed with a state-of-the-art low friction additive system for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. EVEREST Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile or stationary engines.

EVEREST Full Synthetic SAE 10W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SP service classification and is compatible with all prior API categories. EVEREST Full Synthetic SAE 10W-40 motor oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including MB 229.3, RN 0710/0700, VW 502 00 / 505 00, and many other OEM's specifications where a full synthetic API SP motor oil is recommended.

Benefits and Applications

- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Full synthetic oil helps to improve fuel economy
- Superior resistance to sludge and varnish deposit formation

10W-40 Typical Characteristics - V210610

SAE GRADE	Full Syn	10W-40
API SERVICE		SP
API Gravity	ASTM D287	32.08
Flash Point, COC °C/°F	ASTM D92	210 / 410
Pour Point, °C/°F	ASTM D97	-33 / -27.4
Viscosity @ 40°C, cSt	ASTM D445	97
Viscosity @ 100°C, cSt	ASTM D445	15.1
Viscosity Index	ASTM D2270	165
CCS, mPa-sec °C max	ASTM D5293	5049
Total Base No. TBN	ASTM D2896	9.5

Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

API SP

MB 229.3, RN 0710/0700,
VW 502 00 / 505 00



HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.