

Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660

CJ-4 SN

**Premium
Performance**

EVEREST®

SAE 10W-40 HEAVY DUTY DIESEL ENGINE OIL

Everest Heavy Duty Synthetic Blend SAE 10W-40 CJ-4 Diesel Engine Oil is a premium multi-grade diesel engine oil specifically engineered to meet the requirements of naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines used in automotive, heavy duty trucking, construction, mining and farm equipment. It minimizes sludge and varnish formation and provides outstanding anti-wear protection, deposit control, and extends overall engine life under the toughest driving conditions.

Everest Heavy Duty Synthetic Blend SAE 10W-40 CJ-4 Diesel Engine Oil outperforms conventional motor oil and meets or exceeds the American Petroleum Institute (API) CJ-4 / SN service classifications as well as all prior API specifications including CI-4 Plus, CH-4, CG-4, CF-4, CF / SM, SL, and SJ. It has been field tested to be comparable to most American, Asian and European manufacturers' standards including Mack EO-M Plus, Cummins CES 20081, Volvo VDS-4, Caterpillar ECF-3 -2, MB 228 31, JASO DH-2 and other OEM's specifications where an API CJ-4 / SN motor oil is recommended.

Benefits and Applications

- For diesel and gasoline engines exceeds CJ-4 / SN service classifications
- Synthetic Blend motor oil outperforms conventional oil
- Maximum engine cleanliness and protection
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation

Typical Characteristic 10W-40 Heavy Duty CJ-4 Oil

SAE GRADE	Heavy Duty	10W-40
API SERVICE		CJ-4 / SN
API Gravity	ASTM D4052-11	30.9
Flash Point, COC °C/°F	ASTM D92	206 / 402.8
Pour Point, °C/°F	ASTM D97	-40 / -40
Viscosity @ 40°C, cSt	ASTM D445	110.0
Viscosity @ 100°C, cSt	ASTM D445	15.9
Viscosity Index	ASTM D2270	154
CCS, mPa-sec °C max	ASTM D5293	7000 @ -25
Total Base No. TBN	ASTM D2896	9

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

CJ-4 / SN

Meets standards Mack EO-M Plus, Cummins CES 20081, Volvo VDS-4, Caterpillar ECF-3 -2, MB 228 31, JASO DH-2



V210616

HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.