Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660

Premium Performance

EVEREST

Synthetic Blend High Mileage SAE 10W-40 Motor Oil

Everest Synthetic Blend High Mileage SAE 10W-40 Motor Oil is formulated with a low friction additive package designed especially for engines with over 75,000 miles. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against sludge and varnish deposits and provides additional anti-wear protection that helps extend engine life. It is recommended for passenger car, truck, sport utility vehicle and other engines with over 75,000 miles.

Everest Synthetic Blend High Mileage SAE 10W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SP service classification and is compatible with all prior API categories. It has been field tested to be comparable to most American, Asian and European manufacturers' standards including MB 229.3, RN 0710/0700, VW 502.00 / 505.00, and many other OEM's specifications where a synthetic blend API SP motor oil is recommended.

Benefits and Applications

- Everest Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Typical Characteristic 10W-40 Synthetic Blend Oil

SAE GRADE	Syn Blend	10W-40
API SERVICE		SP
API Gravity	ASTM D287	32.55
Flash Point, COC °C/°F	ASTM D92	243 / 469.4
Pour Point, °C/°F	ASTM D97	-41 / -41.8
Viscosity @ 40°C, cSt	ASTM D445	110.55
Viscosity @ 100°C, cSt	ASTM D445	16.06
Viscosity Index	ASTM D2270	156
CCS, mPa-sec °C max	ASTM D5293	7000 @ -25
Total Base No. TBN	ASTM D2896	7.6

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SP

MB 229.3, RN 0710/0700, VW 502 00 / 505 00







API SP

V210618

HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.