

Technical Product Information
 www.usglobalpetroleum.com
 www.everestoil.com
 773-376-9660

4T

Premium
 Performance

EVEREST®

Syn Blend 4T SAE 20W-50 Motorcycle Oil

EVEREST 4T Synthetic Blend Motorcycle SAE 20W-50 Engine Oil is designed specifically for high-temperature, high RPM, 4-stroke engines used in on and off-road motorcycles, ATVs and similar vehicles. It is a premium quality multi-grade engine oil designed with high-tech, low friction performance additives that deliver advanced low temperature fluidity to ensure easy cranking and startup protection. It provides outstanding anti-wear protection, exceptional control and resistance of performance robbing sludge and varnish deposits and provides superior frictional characteristics for maximum power transfer, smooth shifting and superb wet clutch protection even under the most severe riding conditions.

EVEREST 4T Synthetic Blend Motorcycle SAE 20W-50 Engine Oil meets or exceeds API SN service classification and is compatible with all prior API classifications. It has been field tested to be comparable to most American, Asian, and European manufacturers' standards including JASO MA/MA2 many other OEM's specifications where a synthetic blend API SN motorcycle engine oil is recommended.

Benefits and Applications

- For use in on / off-road 4-stroke motorcycles and ATVs
- Enhanced oxidative stability, emission system and wear protection
- Resists breakdown in the most severe engine environments
- Superior wet clutch protection

Typical Characteristic 20W-50 Synthetic Blend Oil

| SAE GRADE | Syn Blend | 20W-50 |
|------------------------|------------|-------------|
| API SERVICE | | SN |
| API Gravity | ASTM D287 | 29.7 |
| Flash Point, COC °C/°F | ASTM D92 | 206 / 402.8 |
| Pour Point, °C/°F | ASTM D97 | -30 / -22 |
| Viscosity @ 40°C, cSt | ASTM D445 | 156.9 |
| Viscosity @ 100°C, cSt | ASTM D445 | 18.6 |
| Viscosity Index | ASTM D2270 | 133 |
| CCS, mPa-sec °C max | ASTM D5293 | 9500 @ -15 |
| Total Base No. TBN | ASTM D2896 | 7.9 |

API SN
 JASO MA/MA2



Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

V230509

HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.