

Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660

CI-4

Premium
Performance

EVEREST®

Heavy Duty Synthetic Blend Engine Oil

Everest Heavy Duty SAE 15W-40 Synthetic Blend Engine Oil is a premium multi-grade oil specifically engineered to meet the requirements of naturally aspirated, turbocharged, or supercharged diesel, gasoline, and propane engines used in automotive, trucking, construction, mining and farm equipment. It helps extend overall engine life by minimizing sludge and varnish formation and providing outstanding anti-wear protection and deposit control even under the toughest driving conditions.

Everest Heavy Duty SAE 15W-40 Synthetic Blend Engine Oil Engine Oil outperforms conventional motor oil and meets or exceeds the American Petroleum Institute (API) CI-4 / SL classifications and all prior API specifications including CH-4, CG-4, CF-4, CF-2, CF and API SJ, and SH. It has been field tested to be comparable to most American, Asian and European manufacturers' standards including Mack EO-M Plus, Cummins CES 20078, Volvo VDS / VDS-2, Caterpillar ECF-1, and power shift transmissions specifying Allison C-3 / C-4, and CAT TO-2 many other OEM's specifications where a heavy duty API CI-4/SL motor oil is recommended.

Benefits and Applications

- For diesel, propane, and gasoline engines, promotes long engine life
- Excellent cold-crank capabilities
- Outstanding anti-wear protection

Typical Characteristic 15W-40 Heavy Duty Synthetic Blend Oil

| SAE GRADE | Heavy Duty | 15W-40 |
|------------------------|---------------|-------------|
| SERVICE GRADE | | CI-4 / SL |
| API Gravity | ASTM D4052-11 | 30.94 |
| Flash Point, COC °C/°F | ASTM D92 | 231 / 447.8 |
| Pour Point, °C/°F | ASTM D97 | -34 / -29.2 |
| Viscosity @ 40°C, cSt | ASTM D445 | 118.3 |
| Viscosity @ 100°C, cSt | ASTM D445 | 15.63 |
| Viscosity Index | ASTM D2270 | 139 |
| CCS, mPa-sec °C max | ASTM D5293 | 4588 @ -20 |
| Total Base No. TBN | ASTM D2896 | 9.34 |

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

CI-4 / SL

Mack EO-M Plus, Cummins
CES 20081, Volvo VDS/-
VDS-2, MAN 3275, CAT
ECF-1, MB 228.32



V210804

HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.