

PETROMERICA

dexos1™ GEN 3 Full Synthetic ULTRA SAE 0W-20 Motor Oil

PETROMERICA DEXOS1™ GEN 3 FULL SYNTHETIC ULTRA SAE 0W-20 MOTOR OIL is formulated from select low-friction, full synthetic base stocks and an advanced technology additive system licensed by General Motors to meet their Global Engine Oil Specification. It provides excellent oxidation stability, superior resistance to sludge formation and varnish deposits, reduces friction and wear at start-up and protects your engine even under the toughest driving conditions. Petromerica dexos1™ GEN 3 Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile and stationary engines.

PETROMERICA DEXOS1™ GEN 3 FULL SYNTHETIC ULTRA SAE 0W-20 MOTOR OIL meets or exceeds stringent GM dexos1™ GEN 3 requirements, ILSAC GF-6A and American Petroleum Institute (API) Resource Conserving SP service classifications as well as all earlier API categories. Petromerica dexos1™ GEN 3 Full Synthetic SAE 0W-20 has been field tested to be comparable to most American, Asian and European manufacturers' standards including GM 6094M, Chrysler MS6395, Ford WSS-M2C947A, and other OEM's specifications where a full synthetic API SP/GF-6A motor oil is recommended.

BENEFITS AND APPLICATIONS

- Full synthetic dexos1™ GEN 3 protection license # D330BCCK299
- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Full synthetic oil helps to improve fuel economy
- Superior resistance to sludge and varnish deposit formation

0W-20 Typical Characteristics - V220207

| SAE GRADE | dexos1™ | 0W-20 |
|------------------------|------------|-------------|
| API SERVICE | | SP / GF-6A |
| API Gravity | ASTM D287 | 35.88 |
| Flash Point, COC °C/°F | ASTM D92 | 227 / 440.6 |
| Pour Point, °C/°F | ASTM D97 | -51 / -59.8 |
| Viscosity @ 40°C, cSt | ASTM D445 | 42.76 |
| Viscosity @ 100°C, cSt | ASTM D445 | 8.106 |
| Viscosity Index | ASTM D2270 | 166 |
| CCS, mPa-sec °C max | ASTM D5293 | 6200 @ -35 |
| Total Base No. TBN | ASTM D2896 | 8.1 |

Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

**API SP
ILSAC GF-6A
dexos1™ GEN 3**

GM 6094M,
Chrysler MS6395,
Ford WSS-M2C947A



dexos1™
GM APPROVED - GEN 3



Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

www.usglobalpetroleum.com

www.petromericaoil.com