

PETROMERICA

4T Semi Synthetic PLUS SAE 15W-50 Motorcycle Engine Oil

Petromerica 4T Semi Synthetic PLUS SAE 15W-50 Motorcycle Engine Oil is designed specifically for high-temperature, high RPM, 4-stroke engines used in on and off-road motorcycles, ATVs and similar vehicles. It is a premium quality multi-grade engine oil designed with high-tech, low friction performance additives that deliver advanced low temperature fluidity to ensure easy cranking and startup protection. It provides outstanding anti-wear protection, exceptional control and resistance of performance robbing sludge and varnish deposits and provides superior frictional characteristics for maximum power transfer, smooth shifting and superb wet clutch protection even under the most severe riding conditions.

Petromerica 4T Semi Synthetic PLUS SAE 15W-50 Motorcycle Engine Oil meets or exceeds SN service classification and is compatible with all prior API classifications. Petromerica 4T Semi Synthetic PLUS SAE 15W-50 Motorcycle Engine Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including JASO MA/MA2 many other OEM's specifications where a synthetic blend SN/SL motorcycle engine oil is recommended.

Benefits and Applications

- For use in on / off-road 4-stroke motorcycles and ATVs
- Meets or exceeds SN and JASO MA/MA2 service
- Resists breakdown in the most severe engine environments
- Fights formation of sludge and varnish deposits that reduce engine life
- Optimum protection over a wide operating temperature
- Excellent wear, corrosion, and rust protection
- Superior wet clutch protection

15W-50 Typical Characteristics - V191211

SAE GRADE	Syn Blend	15W-50
API SERVICE		SN/SL
API Gravity	ASTM D287	33.03
Flash Point, COC °C/°F	ASTM D92	208 / 406.4
Pour Point, °C/°F	ASTM D97	-35 / -31
Viscosity @ 40°C, cSt	ASTM D445	133.8
Viscosity @ 100°C, cSt	ASTM D445	18.49
Viscosity Index	ASTM D2270	155
CCS, mPa-sec °C max	ASTM D5293	7000 @ -20
Total Base No. TBN	ASTM D2896	8.65

Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

API SN/SL

JASO MA/MA2



Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

www.usglobalpetroleum.com

www.petromericaoil.com