

PETROMERICA

Full Synthetic ULTRA DEXRON®-VI ATF

PETROMERICA FULL SYNTHETIC ULTRA DEXRON®-VI AUTOMATIC TRANSMISSION FLUID is a fully licensed DEXRON®-VI ATF (License Number: J-60189), the only GM® approved specification for vehicles of model years 2006 and newer. Petromerica Multi-Vehicle DEXRON®-VI ATF is a high performance universal ATF providing superior oxidation control, extended service intervals, maximum year-round low and high temperature performance, improved fuel economy and shear stability. It is suitable for use where GM DEXRON®-VI, DEXRON® III/III(H)/IIE, DEXRON® II, Ford MERCON® LV, Allison®, Honda® Z-1, Hyundai/Kia SP-II/III/IV, Toyota WS,T-III, T-IV, Mercedes Benz®, or Nissan® Matic C/D/J/K/S Fluids are recommended.

**Not for used in extended drain heavy duty diesel, Type F, CVT or DCT applications.*

APPROVALS, APPLICATIONS AND BENEFITS

- GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H, VI • Ford MERCON®, MERCON® LV • Acura ATF-Z1 • Audi 5 HP LT71141
- Chrysler (Mopar) ATF-Plus, ATF +3, ATF +4 • Allison C-3, C-4, TES-295, TES-389 • CAT TO-2 • Daewoo LT 71141 • Esso LT 71141
- BMW • Honda Z-1 • Hyundai/Kia SP-II/III/IV • JASO • FIAT T-IV type, JWS 3309 • Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24
- ISUZU BESCO ATF-II /III • Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1 • MINI COOPER T-IV • Opel (all vehicles) • Peugeot ZF 4HP20
- Mercedes • Mitsubishi • Nissan/ Infinity Matic Fluids • Toyota ATF D-II/D-III/T-III/T-IV/WS • VW 5 HP, G-055-025 A2 (JWS 3309)
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141 • Saab T-IV • Scion (all vehicles) • Shell 3403, M115, LA 2634 • Subaru ATF • Suzuki ATF
- Vickers M2950-S, I-286-S • Voith • Volvo CE 97340 • ZF all 3 & 4 speed transmission • and many more
- Superior all-temperature, year-round protection and high performance
- Advanced anti-wear protection and shear stability
- Smoother shifting, protection against shudder
- Extended life of service and performance

Typical Characteristics - ATF-III - V200407

GRADE	Test Method	ATF-III / DEX-III
Color	Visual	Red
Viscosity @ 100°C, cSt	ASTM D445	5.8
Viscosity @ 40°C, cSt	ASTM D445	29.5
Viscosity Index	ASTM D2270	145
Pour Point, °C/°F	ASTM D97	-51 / -59.8
Flash Point, COC °C/°F	ASTM D92	220 / 428
API Gravity	ASTM D287	36.0
Brookfield Vis.cP @ -40°C	ASTM D2983	10,000

Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

DEXRON
APPROVED
License Number: J-60189

Suitable for:

GM DEXRON®-VI
DEXRON® III/III(H)/IIE
Nissan® Matic Fluids
Hyundai/Kia SP-II/III/IV
Toyota WS, T-III, T-IV
Ford MERCON® LV
Mercedes Benz®
Honda® Z-1
Allison® C-3, C-4
Volvo CE 97340



Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

www.usglobalpetroleum.com

www.petromericaoil.com