



# MAXCOOL 50/50 Antifreeze / Coolant

## iLast Premium MAXCOOL 50/50 Antifreeze/Coolant

Used as directed provides superior performance in virtually every light duty Application - including light duty trucks. Compatible with Dexcool® Coolant. The perfect protection choice for:

- All Season Freeze-up/Boil Over
- Rust and Corrosion
- Scale Build Up
- Sludge/Clogging

iLAST MAXCOOL meets ASTM D-3306 for all light duty applications and is low silicate and blended with advanced Hybrid Organic Technologies.

### Advantages

- Meets ASTM D-3306 and Long Life specifications.
- Safe for use with all engine metals, including Aluminum.
- Light Duty Use - 150,000 miles.
- Compatible with hybrid and OAT coolants - including Dexcool®
- Safe for use with all engine metals, including aluminum.
- Suitable for American, European and Asian models
- For safety purposes all iLAST antifreeze is blended with a bittering agent.

### Specifications

iLast MAXCOOL 50/50 is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- ASTM D-3306
- GM 1825M
- GM 1899M
- Chrysler MS 7170
- Ford ESE-M97B44-A
- JIS K 2234
- Ford WSS-M97B51-A1
- TMC RP302C
- GM 6277M



## TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD	BOIL OVER PROTECTION			
Appearance	Visual	Orange/Red	Type of Coolant Test	Atmospheric Pressure	14LB. cap	15LB. cap
Specific Gravity at 60/60°F	1.053-1.083	D 1122	Coolant Boiling	224°F	262°F	265°F
Freeze Point, at 50% max	-34°F	D-3321	Coolant Freezing	-34°F	-34°F	-34°F
pH at 50% Solution	8.5-10.0	D-1287				
Reserve Alkalinity min.	2.5	D-1121				
Foam Test	150ml/5 sec	D-1881				

Available in Gallon jugs, Drums, Totes or Bulk.