



SYNTHETIC DOT 3 BRAKE FLUID

EXTENDED LIFE

Technical Data Sheet



V170303

MOTOR VEHICLE BRAKE FLUID FOR DRUM & DISK BRAKES

iLast Synthetic DOT 3 Brake Fluid has a minimum boiling point of 450°F. It meets and exceeds DOT 3 and all other Federal and SAE specifications and standards for motor vehicle brake fluids. Mixes with all DOT 3 approved brake fluids. Designed for use in all disc, drum and ABS brake systems requiring DOT 3 motor vehicle brake fluid.



MADE IN USA

- 12-Ounce - FPiL0003
- 1-Gallon - FPiL0004
- 5-Gallon - FPiL0005
- 55-Gallon - FPiL0006

Typical Properties

Flash Point	>275 °F
Boiling Point	>450 °F
Specific Gravity	1.0
Appearance	Yellow to Amber
Odor	Mild
Flammability	Low Flammability
Plastic Safe	Yes
Propellant	Not Applicable

Typical test data are average values only. Minor variations, which do not affect performance, may occur. As always, you should consult your owner's manual to verify the proper fluid recommendation for your particular vehicle.

+1 773.376.9660 usglobalpetroleum.com

Manufactured by
US Global Petroleum
Franklin Park, IL 60131

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.